## **CRUD Operations Cheat Sheet**

This cheat sheet summarizes the essential Create, Read, Update, and Delete (CRUD) operations for files and directories across Linux, PowerShell, and Windows Command Prompt (CMD). Keep this handy as you navigate different command-line environments!

Operation	Linux Commands	PowerShell Cmdlets / Operators	Windows CMD Commands / Operators
CREATE	<pre>touch file.txt (empty file) mkdir folder_name mkdir -p path/to/folder (create parents)</pre>	New-Item -ItemTvpe File file.txt New-Item -ItemType Directory folder_name Aliases: mkdir	<pre>tvpe NUL &gt; file.txt (empty file) mkdir folder_name Aliases: md</pre>
READ	<pre>cat file.txt (full content) less file.txt (scrollable content) head -n X file.txt (first X lines) tail -n X file.txt (last X lines)</pre>	Get-Content file.txt  Aliases: cat, type	type file.txt
UPDATE	<pre>echo "text" &gt;&gt; file.txt (append) nano file.txt / vi file.txt (editor) echo "new text" &gt; file.txt (overwrite)</pre>	Add-Content -Value "text" file.txt (append) Set-Content -Value "text" file.txt (overwrite) Operators: >> (append), > (overwrite)	<pre>echo "text" &gt;&gt; file.txt (append) echo "new text" &gt; file.txt (overwrite)</pre>
DELETE	<pre>rm file.txt rmdir empty_folder rm -r folder_with_stuff (recursive) Safety: rm -ri folder (recursive, interactive)</pre>	Remove-Item file.txt Remove-Item folder name Remove-Item -Recurse folder_with_stuff Aliases: rm, rmdir Optional: -Force	<pre>del file.txt rd emptv folder / rmdir empty_folder rd /s folder_with_stuff (recursive) Optional: rd /s /q folder (recursive, quiet)</pre>